

Part Number	Sensor Size** (mm)	EFL (mm)	BFL (mm)	F Number	Field of Vision (deg)			Opt. Des.	Lumination Intensity @1.0 Field	Dimension (mm)		Flange Back Length (mm)	Barrel Mounting Thread
					Hori.	Vert.	Diag.			Dia	Lenght		
E11474-1	4.0	4.0	5.64	2.0	46.2	34.6	53.0	-8.0%	64.00%	14	15.3	4.84	M12xP0.5
E11474-2	4.8	4.0	5.64	2.5	51.9	46.2	68.7	-12.0%	46.50%	14	15.3	4.84	M12xP0.5
E11474-3	4.8	4.0	5.64	2.0	51.9	46.2	68.7	-12.0%	46.50%	14	15.8	4.84	M12xP0.5
E11474-4	4.8	4.0	5.64	2.0	51.9	46.2	68.7	-12.0%	46.50%	14	15.8	4.84	M12xP0.5
E11474-5	4.8	4.0	5.64	2.0	51.9	46.2	68.7	-12.0%	46.50%	14	15.8	4.84	M12xP0.5
E11474-6	4.8	4.0	5.64	2.0	51.9	46.2	68.7	-12.0%	46.50%	14	15.8	4.84	M12xP0.5
E11474-7	6.0	4.0	5.64	2.0	68.7	51.9	84.3	-19.0%	30.20%	14	15.8	4.84	M12xP0.5
E11474-8	6.0	4.0	5.64	1.8	68.7	51.9	84.3	-19.0%	30.20%	14	15.8	4.84	M12xP0.5
E11474-9	6.0	4.0	5.64	2.0	68.7	51.9	84.3	-19.0%	30.20%	14	15.8	4.84	M12xP0.5
E11474-10	6.0	4.0	5.64	2.0	68.7	51.9	84.3	-19.0%	30.20%	14	17.3	3.40	M12xP0.5
E11474-11	6.0	4.0	5.64	2.0	68.7	51.9	84.3	-19.0%	30.20%	14	17.3	3.40	M12xP0.5
E11474-12	6.0	4.0	5.64	2.0	44.2	51.9	84.3	-19.0%	30.20%	14	17.3	3.40	M12xP0.5
E11474-13	6.3	6.0	6.85	2.0	44.2	33.2	56.1	-6.0%	60.70%	14	14.4	6.30	M12xP0.5
E11474-14	6.3	6.0	6.85	1.8	44.2	33.2	56.1	-6.0%	60.70%	14	14.4	6.30	M12xP0.5
E11474-15	6.6	6.0	6.85	1.8	44.2	33.2	56.1	-6.0%	60.70%	14	17.1	6.30	M12xP0.5
E11474-16	6.3	6.0	6.85	1.8	44.2	33.2	56.1	-6.0%	60.70%	14	14.4	6.30	M12xP0.5
E11474-17	6.6	6.0	6.85	1.8	44.2	33.2	56.1	-6.0%	60.70%	14	14.4	6.30	M12xP0.5
E11474-18	6.0	5.5	5.51	5.0	57.1	43.2	70.5	n/a	44.50%	14	6	3.18	M10xP0.5
E11474-19	6.0	5.5	5.51	3.5	57.1	43.2	70.5	n/a	44.50%	14	6	3.18	M12xP0.5
E11474-20	6.0	5.5	5.51	5.0	57.1	43.2	70.5	n/a	44.50%	14	6	3.18	M12xP0.5
E11474-21	6.0	5.5	5.51	5.0	57.1	43.2	70.5	n/a	44.50%	M12	4.6	4.20	M12xP0.5
E11474-22	6.0	3.7	3.85	4.0	75.6	57.5	91.8	n/a	23.50%	14	4.3	2.60	M10xP0.5
E11474-23	6.0	3.7	3.85	4.0	75.6	57.5	91.8	n/a	23.50%	14	4.3	2.60	M12xP0.5
E11474-24	6.0	3.7	3.85	4.0	75.6	57.5	91.8	n/a	23.50%	M12	4.3	2.60	M12xP0.5
E11474-25	6.0	5.6	4.2	2.0	49.4	37.0	61.5	-9.0%	54.50%	10	6.5	3.50	M8.0xP0.5
E11474-26	6.0	5.6	4.2	2.0	49.4	37.0	61.5	-9.0%	54.50%	12	6.6	3.50	M8.0xP0.5
E11474-27	6.0	5.6	4.2	1.8	49.4	37.0	61.5	-9.0%	54.50%	10	6.5	3.50	M8.0xP0.5
E11474-28	6.5	5.6	4.2	1.8	51.2	38.8	65.1	-10.2%	50.50%	14	8.8	2.10	M12xP0.5
E11474-29A	6.0	6.0	8.85	2.0	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5
E11474-29B	7.5	6.0	8.85	2.0	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5

E11474-30A	6.0	6.0	8.85	1.8	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5
E11474-30B	7.5	6.0	8.85	1.8	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5
E11474-31A	6.0	6.0	8.85	1.8	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5
E11474-31B	7.5	6.0	8.85	1.8	46.0	34.5	57.1	-8.0%	59.50%	14	15.8	8.30	M12xP0.5
E11474-32	6.0	3.6	5.6	2.0	76.0	57.9	95.0	-20.2%	20.80%	14	15.7	5.00	M12xP0.5
E11474-33	6.0	3.6	5.6	1.8	76.0	57.9	95.0	-20.2%	20.80%	14	15.7	5.00	M12xP0.5
E11474-34	6.0	2.5	5.52	2.0	105.8	82.8	123.6	-35.7%	5.00%	14	19.5	4.77	M12xP0.5
E11474-35	6.0	2.5	5.52	1.8	105.8	82.8	123.6	-35.7%	5.00%	14	19.5	4.77	M12xP0.5
E11474-36A	6.0	6.2	4.66	2.8	42.9	32.6	52.3	-1.5%	64.50%	14	6.45	4.10	M12xP0.5
E11474-36B	5.5	6.2	4.66	2.8	42.9	32.6	52.3	-1.5%	64.50%	14	6.45	4.10	M12xP0.5
E14006-1	n/a	10.02	6.356	3.0	n/a	n/a	43.98	11.13%	n/a	n/a	11.40	3.51	M12x0.5P
E14006-2	n/a	2.69	5.10	2.0	n/a	n/a	140	-39.6%	n/a	n/a	18.14	4.7	M12x0.5P
E14006-3	n/a	3.10	5.30	2.4	n/a	n/a	120	-44.2%	n/a	n/a	16.37	4.66	M12x0.5P
E14006-4	n/a	3.47	2.94	2.8	n/a	n/a	56	-7.0%	n/a	n/a	6.87	2.04	M12x0.5P
E14006-5	n/a	3.47	2.94	2.8	n/a	n/a	56	-7.0%	n/a	n/a	4.46	2.04	M12x0.5P
E14006-6	n/a	3.47	2.94	2.8	n/a	n/a	56	-7.0%	n/a	n/a	19.83	2.04	M12x0.5P
E14006-7	n/a	3.47	2.94	2.8	n/a	n/a	56	-7.0%	n/a	n/a	13.76	2.04	M12x0.5P
E14006-8	n/a	3.47	2.94	2.8	n/a	n/a	56	-7.0%	n/a	n/a	4.46	2.04	M9.0x0.5P
E14006-9	n/a	3.60	4.90	2.4	n/a	n/a	92	-27.3%	n/a	n/a	15.90	4.31	M12x0.5P
E14006-10	n/a	3.60	4.45	2.0	n/a	n/a	92	-31.6%	n/a	n/a	15.45	5.00	M12x0.5P
E14006-11	n/a	3.80	3.29	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.10	2.05	M12x0.5P
E14006-12	n/a	3.80	3.29	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.10	2.05	M12x0.5P
E14006-13	n/a	3.80	3.53	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.10	2.27	M12x0.5P
E14006-14	n/a	3.80	3.53	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.10	2.27	M12x0.5P
E14006-15	n/a	3.80	3.53	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.10	2.27	M12x0.5P
E14006-16	n/a	3.90	3.53	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.20	2.20	M12x0.5P
E14006-17	n/a	3.90	3.53	2.0	n/a	n/a	92,68	-22.7%	n/a	n/a	8.20	2.20	M12x0.5P
E14006-18	n/a	4.35	4.54	2.4	n/a	n/a	50	-7.5%	n/a	n/a	5.30	3.63	M12x0.5P
E14006-19	n/a	4.30	6.47	2.0	n/a	n/a	78,60	-21.5%	n/a	n/a	17.10	4.17	M12x0.5P
E14006-20	n/a	4.39	3.14	2.0	n/a	n/a	73,62.4	-15.3%	n/a	n/a	8.26	2.59	M12x0.5P
E14006-21	n/a	4.39	3.14	2.0	n/a	n/a	73,62.4	-15.3%	n/a	n/a	8.26	2.59	M12x0.5P
E14006-22	n/a	4.39	3.14	2.0	n/a	n/a	73,62.4	-15.3%	n/a	n/a	8.26	2.59	M12x0.5P

E14006-23	n/a	4.39	3.38	2.0	n/a	n/a	73,62.4	-15.3%	n/a	n/a	8.96	2.20	M12x0.5P
E14006-24	n/a	4.39	3.38	2.0	n/a	n/a	73,62.4	-15.3%	n/a	n/a	8.96	2.20	M12x0.5P
E14006-25	n/a	4.63	4.95	2.8	n/a	n/a	56	-5.78%	n/a	n/a	12.33	2.50	M12x0.5P
E14006-26	n/a	5.58	5.84	2.4	n/a	n/a	60,45.6	-7.7%	n/a	n/a	5.30	4.17	M9.0x0.5P
E14006-27	n/a	5.58	5.84	2.4	n/a	n/a	60,45.6	-7.7%	n/a	n/a	7.30	1.61	M12x0.5P
E14006-28	n/a	5.58	5.84	2.4	n/a	n/a	60,45.6	-7.7%	n/a	n/a	5.30	4.17	M12x0.5P
E14006-29	n/a	6.00	6.46	2.0	n/a	n/a	60	-3.32%	n/a	n/a	14.40	4.95	M12x0.5P
E14006-30	n/a	6.60	8.17	1.8	n/a	n/a	53.7	-10.14%	n/a	n/a	16.30	7.22	M12x0.5P
E14006-31	n/a	6.50	7.96	2.4	n/a	n/a	55	-10.57%	n/a	n/a	11.60	3.70	M12x0.5P
E14006-32	n/a	7.09	5.19	1.8	n/a	n/a	59.9	-12.3%	n/a	n/a	14.41	3.93	M12x0.5P
E14006-33	n/a	7.07	2.95	2.4	n/a	n/a	52	-3.26%	n/a	n/a	7.99	1.55	M12x0.5P
E14006-34	n/a	7.07	2.95	2.4	n/a	n/a	52	-3.26%	n/a	n/a	9.30	1.55	M12x0.5P
E14006-35	n/a	7.07	2.95	2.4	n/a	n/a	52	-3.26%	n/a	n/a	13.45	1.55	M12x0.5P
E14006-36	n/a	7.27	4.41	2.8	n/a	n/a	48.8	-2.73%	n/a	n/a	9.61	2.45	M12x0.5P
E14006-37	n/a	7.27	9.28	2.4	n/a	n/a	55	-10.49%	n/a	n/a	13.29	2.81	M12x0.5P
E14006-38	n/a	7.90	10.19	2.4	n/a	n/a	55	-10.74%	n/a	n/a	13.30	3.78	M12x0.5P
E14006-39	n/a	7.80	5.09	2.0	n/a	n/a	40	-4.21%	n/a	n/a	13.50	4.46	M12x0.5P
E14006-40	n/a	8.70	7.60	2.8	n/a	n/a	53.13	-0.96%	n/a	n/a	15.33	6.40	M12x0.5P
E11887-1A	6.0	2.1	5.6	2.0	n/a	n/a	150.0	n/a	n/a	n/a	19.1	n/a	n/a
E11887-1B	4.0	2.1	5.6	2.0	n/a	n/a	120.0	n/a	n/a	n/a	19.1	n/a	n/a
E11887-2A	6.0	2.5	5.5	2.0	n/a	n/a	130.0	n/a	n/a	n/a	19.5	n/a	n/a
E11887-2B	4.0	2.5	5.5	2.0	n/a	n/a	100.0	n/a	n/a	n/a	19.5	n/a	n/a
E11887-3A	6.0	2.9	5.5	2.0	n/a	n/a	120.0	n/a	n/a	n/a	15.3	n/a	n/a
E11887-3B	4.0	2.9	5.5	2.0	n/a	n/a	96.0	n/a	n/a	n/a	15.3	n/a	n/a
E11887-4A	6.0	4.3	5.58	1.8	63.0	47.5	78.0	n/a	n/a	14	14.1	4.52	M12xP0.5
E11887-4B	4.0	4.3	5.58	1.8	n/a	n/a	60.0	n/a	n/a	14	14.1	4.52	M12xP0.5
E11887-5A	6.0	3.7	3.5	4.5	n/a	n/a	90.7	n/a	n/a	n/a	4.3	n/a	n/a
E11887-5B	4.0	3.7	3.5	4.5	n/a	n/a	68.0	n/a	n/a	n/a	4.3	n/a	n/a
E11887-6	6.0	5.5	4.5	4.5	n/a	n/a	50.0	n/a	n/a	n/a	4.3	n/a	n/a
E11887-7A	6.0	3.7	5.73	2.0	74.2	55.8	92.7	n/a	n/a	14	14.2	5.58	M12xP0.5
E11887-7B	4.0	3.7	5.73	2.0	51.0	38.9	69.6	n/a	n/a	14	14.2	5.58	M12xP0.5
E11887-7C	1/5-in	3.7	5.73	2.0	n/a	n/a	57.3	n/a	n/a	14	14.2	5.58	M12xP0.5

E11887-8*	6.0	6.0	4.5	1.8	45.9	34.8	60.0	<7%	n/a	14	11.7	2.70	M12xP0.5
E11887-9	6.0	6.0	8.1	1.8	n/a	n/a	60.0	n/a	n/a	n/a	15.2	n/a	n/a
E11887-10	6.0	8.0	5.2	2.0	n/a	n/a	40.0	n/a	n/a	n/a	13.8	n/a	n/a
E11887-11	6.0	12.0	6.9	2.0	n/a	n/a	26.0	n/a	n/a	n/a	31.2	n/a	n/a
E11887-12	6.0	16.0	7.5	1.6	n/a	n/a	19.0	n/a	n/a	n/a	34.7	n/a	n/a
E11887-13	6.0	4.0	5.7	2.0	n/a	n/a	81.0	n/a	n/a	n/a	19.1	n/a	n/a
E11887-14	6.0	6.0	3.6	1.8	n/a	n/a	60.2	n/a	n/a	n/a	29.7	n/a	n/a
E11887-15	6.0	8.0	7	2.8	n/a	n/a	40.0	n/a	n/a	n/a	30.2	n/a	n/a
E11887-16A	4.0	3.9	4.32	2.8	n/a	n/a	64.7	n/a	n/a	n/a	4	n/a	n/a
E11887-16B	1/5-in	3.9	4.32	2.8	n/a	n/a	52.1	n/a	n/a	n/a	4	n/a	n/a
E11887-17A	4.0	3.9	4.32	2.8	52.1	39.3	64.7	n/a	n/a	14	11.5	1.99	M12xP0.5
E11887-17B	1/5-in	3.9	4.32	2.8	41.8	31.5	52.1	n/a	n/a	14	11.5	1.99	M12xP0.5
E11887-18A	6.0	5.2	5.755	2.8	n/a	n/a	64.8	-9.0%	n/a	14	14.38	3.52	M12xP0.5
E11887-18B	4.0	5.2	5.755	2.8	39.2	29.5	48.9	-4.8%	n/a	14	14.38	3.52	M12xP0.5
E11887-19*	4.0	6.7	5.65	2.4	n/a	n/a	37.88	n/a	n/a	n/a	13.8	n/a	n/a
E11887-20*	4.0	6.7	5.65	2.4	n/a	n/a	37.88	n/a	n/a	n/a	11.94	n/a	n/a

EFL = Effective Focal Length (mm)

BFL = Back Focal Length (mm)

\*Can be used with both CMOS and CCD cameras