

STANDARD CORNER CUBES								
Angle Tolerance (arc sec.)	Material	Surface Quality (Scratch / Dig)	Diameter (mm)	Diameter Tolerance (mm)	Height (mm)	Height Tolerance (mm)	Surface Flatness	Chamfer (mm)
2,5,or 10	BK7	60/40	7.16	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	12.7	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	25.4	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	38.1	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	50.8	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	63.5	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2
2,5,or 10	BK7	60/40	76.2	+0.00/-0.10	*	±0.25	1/4,1/8 wavelength	0.2

\*Height can be specified by customer.